Adapter head with connection by screwing SODEREL



30 years at your service



Adapter head with connection by screwing



Adapter with short screwing head

To be screwed at best on your tanks, our adapters are equipped with one of the three screwing heads:

- the short screwing head (standard)
- the long screwing head
- the extra-short screwing head

Angle (handle/screwing head)	90°
Engine	pneumatic

Advantages

The adapter head is modifiable on demand. The body of the adapter is dimensioned according to the accessibility and the specifications of your tanks to be tested.

Handling ease:

- . Positioning facilitated by the screwing head and its cen tring device
- . Optimized weight
- . Controlled and precise torque of screwing and unscrewing (pressure sensors)

Optimal tightness:

. Homogeneous support of the joint on the contact surface of the tank

Security:

. Possibility of manually unscrewing in the event of power supply failure

Fast maintenance:

- . Easy and fast disassembling and replacement of the screwing head, of the joint and of the centring device.
- . No joint of maintenance on the testline
- . Fast change of the screwing head

Economical:

. Only one adapter for several types of tanks (*)

Applications*

Power steering

. Brake


Engine cooling liquid



Patent N°: EP 1 538 125 B1

Adapter head with connection by screwing

Exploded view of the various screwing heads



Adapter with short screwing head



Adapter with long screwing head



Adapter with extra-short screwing head

Products

We propose you our adapters in various forms:

Adapters

After the study of an existing installation, we can carry out modifications on the level of the power supply (air, electricity) and of the program in order to adapt the machine to our technology.



Off-Line systems

Our off-line machines for use in repair area are designed to use one adapter for the tests of the three tanks: engine cooling liquid, brake, power steering.



On-Line systems

On the assembly lines our machines are equipped with the technology of the adapter head with screwing system.



Option: Centring device adapted to the type of tank to facilitate the installation of the adapter.



Patent N°: EP 1 538 125 B1

A network

WEST Area

Rennes Fax. +33(0)299 771 290 agence.rennes@soderel.com



ILE DE FRANCE

Aulnay-sous-Bois Fax. +33(0)148 657 045 agenceparis@soderel.com

SODEREL SAS

10, rue du coteau - Z.I. Ouest F- 54180 Heillecourt Tel. +33(0)383 55 66 66 Fax. +33(0)383 55 66 67

EAST Area

Sochaux Fax. +33(0)381 945 280 agence.sochaux@soderel.com Pont -à-Mousson Fax. +33(0)383 812 567 e.girardot@soderel.com

SOUTH Area

Tarascon Fax. +33(0)490 915 389 agence.sud@soderel.com

SODEREL SK (Slovakia)

Modra Tél. +421 336 474 341 Fax. +421 336 474 378 soderel.sk@soderel.com

Head office: Soderel SAS. Contact: Info@soderel.com. Web site: www.soderel.com